

The CP-3200E is a keypad panel arranged to operate as an XY panel allowing control of any input or output, with up to four levels of breakaway.

Advanced programming control enables the CP-3200E also to be configured to control five destinations without breakaway or a single destination with four levels of breakaway.

The CP-3200E is normally used as a master XY panel in engineering or MCR type applications where access to any input or output is required.

### ►Features & Benefits

- XY mode with four levels of breakaway
- Five destination mode with a TAKE button for each destination but without breakaways
- Single destination mode with five levels of breakaway
- 24 + 6 button keypad for source and destination names
- High brightness vacuum fluorescent alphanumeric display with better viewing angles than LCD types
- Source names can be up to seven characters long
- Destination names can be up to eight characters long
- In use displays for all levels plus preset
- All buttons fully programmable for different functions such as LOCK
- TAKE button optionally causes the source in use and preset displays to toggle
- Optional NEXT and Previous buttons can be assigned to scroll through the available sources and destinations
- Camera joystick override on any eight inputs, with momentary or latching action
- Supports Qlink for legacy router control. Directly connects to most Evertz® routers for simple router control. Contact factory to ensure support
- Supports Ethernet for connection to MAGNUM Router Control system (Please contact the Factory to obtain a list of Routers which can support Ethernet panels directly)



### ►Specifications

<p><b>Control:</b></p> <p>Joystick: 8 Parallel contact closures, TTL levels (GPI) D9 male</p> <p>Qlink: 75Ω coaxial connection for direct connection to routers BNC, "T" adapter and termination required</p> <p>Ethernet: Standard Ethernet interface for connection to MAGNUM Router Control system. RJ45. (Please contact the Factory to obtain a list of Routers which can support Ethernet panels directly)</p>	<p><b>Electrical:</b></p> <p>Voltage: Auto-ranging 100 ↔ 240V AC, 50/60Hz</p> <p>Power: 40W</p> <p>Fuse Rating: 250V, 1A, time delay</p> <p><b>Physical:</b></p> <p>Height: 3.5" (89 mm) 2 RU standard rack height</p> <p>Width: 19" (483 mm) 19" Rack Mount</p> <p>Depth: 3.5" (89 mm) not including connectors</p> <p>Weight: 4 lbs. (1.81 kg)</p> <p>Operating Temp.: 0-40°C</p>	<p><b>Desk Top Mounting (Optional):</b></p> <p>Panel Depth: 1.4" (35mm)</p> <p>Chassis Depth: 3.5" (89mm)</p> <p>Distance from Panel to Chassis: 40" (1m)</p> <p><b>Compliance:</b></p> <p>Safety: TÜV listed, complies with EU safety directives</p> <p>EMI/RFI: Complies with FCC Part 15 Class A regulations Complies with EU EMC directive</p>
--	---	--

### ►Ordering Information

*Note: These part numbers refer to the hardware only. Precise operation is determined by the configuration of the control panel.*

**CP-3200E** Control Panel 2RU with XY Keypad and Display

#### Ordering Options

**+2PS** Redundant Power Supply

#### Accessories

**CP-3200E-DMK** Desk Mount Kit for CP-3200E