



**DreamCatcher™**  
**DC-LITE-CLIENT**  
Desktop Logging and Editing Station

The **DreamCatcher™ Lite Client** is a portable client that provides full access to the **DreamCatcher™** cluster. The compact design allows for logging, editing and content management controls from an intuitive user interface. The addition of a **DC-LITE-CLIENT** to any **DreamCatcher™** cluster provides a resource that will enhance the quality of any production.

The **DC-LITE-CLIENT** allows a single operator to log for an entire production through a graphical interface quickly and accurately. Through the **DreamCatcher™** 10GbE interface the **DC-LITE-CLIENT** provides instant access to all content on the network for effective logging capabilities.

The **DC-LITE-CLIENT** provides another powerful interface for skilled editors to craft their story. The portable client provides access to the **DreamCatcher™** revolutionary editing platform without tying up valuable operation stations. The intuitive touch interface also allows editors to contribute content without requiring in-depth editing knowledge.

The **DreamCatcher™** 10GbE cluster allows the **DC-LITE-CLIENT** unprecedented access to content on the **DreamCatcher™** network, attached storage or network share storage. Using a **DC-LITE-CLIENT** station a single operator can efficiently manage the flow of content for an entire production.

## FEATURES & BENEFITS

- An intuitive touch interface
- Compact, portable design
- Control over any remote output
- Support for high-frame-rate camera playout
- Remote viewing of any input on the **DreamCatcher™** 10GbE network
- Integrated multiviewer
- Graphical logging and metadata insertion tools
- Integrated search engine across a federated database
- Bin organization for simple content management
- Control over the combined transcoding power of the **DreamCatcher™** network

# **DC-LITE-CLIENT**

## Desktop Logging and Editing Station

### SPECIFICATIONS

---

#### Ethernet

2x 1GbE

Connector Type:

DreamCatcher™ SFPs, RJ-45

#### Ports

3x USB 3.0, 2x USB 2.0, 1x USB-C

#### Control

User Interface:

VUE configurable UI

#### Electrical

Voltage:

AC 100-240V, 47-63Hz

Current:

8-4A

### ORDERING INFORMATION

---

**DC-LITE-CLIENT**

**DreamCatcher™** Lite Client